




# MDTE Series

## Wire Wound Molded SMD Power Inductors

### Size 7020



#### FEATURES



- a
- V V
- V aV
- V
- V C V
- a
- a V

#### APPLICATION

- V ,
- V

Dimensions: [mm]

Land Pattern: [mm]




Electrical Properties:

							, ,
						:	,
					19	:	,
			:			,	,
, :	, :					.	,
					11	:	,

Saturation Current will cause L to drop approximately 30%

Temperature Rise Current: The actual value of DC current when the temperature rise is  $\Delta T=40^{\circ}\text{C}$

## Soldering Reflow:



Preheat condition: 150 ~200°C / 60~120 sec.

Allowed time above 217°C: 60~90 sec.

Max temperature: 260°C.

Max time at max temperature: 10 sec.


Allowed Reflow time: 2x max.

## Packaging Information:

### Tape Dimension:

Series	A0 (mm)	B0 (mm)	D (mm)	P0 (mm)	P1 (mm)	W (mm)	K0 (mm)	E (mm)	T (mm)
MDTE7020	8.2±0.1	8.0±0.1	1.5±0.1	4.0±0.1	12.0±0.1	16.0±0.3	2.3±0.1	1.75±0.1	0.35±0.05

### Peel force of top cover tape:



The peel force of top cover tape shall be between 0.1 to 1.3 N



Reel Dimension: [mm]



Packaging Quantity: